



## WUXGA High Brightness Installation Projector

### FEATURES

- HD WUXGA resolution (1920 x 1200)
- 5000 ANSI Lumens and 2000:1 contrast ratio
- DLP® and BrilliantColor™ technologies for detailed image quality
- Centered lens for easy planning & installation
- Three Interchangeable lens options for greater installation flexibility
- Horizontal and vertical lens shift, (also on fixed, short lens)
- Connectivity options including: HDMI v1.4a, DisplayPort, VGA-Out, RJ45 and RS-232
- DisplayPort connector for digital video signals
- Built-in 12V trigger for screen and/or blinds control
- Audio ready with 2x3W stereo speakers



## Combine high performance and rich functionality with simple handling

The D5380U offers a range of features that makes it the ideal projector choice for the professional installation market. In addition to a high brightness of 5000 ANSI lumens, the WUXGA image resolution delivers excellent image quality for full HD video, presentations, display of charts and graphs in addition to High Definition engineering-, graphic and design tools. With the installer in mind the D5380U features horizontal and vertical lens shift, central lens design, 3 lens options and a comprehensive range of connectivity options. The D5380U is also Crestron RoomView ready.



## D5380U-WNL SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	5000
	<b>Native Resolution</b>	WUXGA (1920 x 1200)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x 1200) @60Hz
	<b>Native Aspect Ratio</b>	16:10
	<b>Contrast Ratio</b>	2,000:1
	<b>Keystone Correction</b>	Vertical +/- 40°
Optical	<b>Throw Ratio</b>	1.54 - 1.93:1 (Std lens)
	<b>Zoom Ratio</b>	1.25x (Std lens)
	<b>Lens Shift ( Based on Full Image Height)</b>	Vertical: -20% / +110%, Horizontal: +/- 5%
	<b>Image Size (Diagonal)</b>	30
	<b>Projection Distance</b>	1.5 - 7 m
	<b>Projection Lens</b>	F = 2.46 - 2.56 f = 22.82 - 28.49 mm
	<b>Offset (Based on Full Image Height)</b>	Manual Lens Shift
Features	<b>Features</b>	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock, Presentation Timer, Wall Color Correction, Instant On/Off
Compatibility	<b>Video</b>	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (2), HDMI v1.4b , Display Port, DVI-D, Component (5 BNC) (RGBHV) , Component (YPbPr RCA x 3), S-Video, Composite Video, Audio-In (RCA) (2), Audio-In (Mini-Jack) (2), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, IP Telnet Capable Over RJ-45, 12v Trigger (3.5mm mini Jack), RS-232, 3D-Sync, USB A (for 5V/1.5A power only), Remote Jack(wire remote)
General	<b>Dimensions (W x D x H)</b>	431 x 344 x 181 mm
	<b>Weight</b>	8,6
	<b>Power</b>	Supply: AC 100 - 240V Consumption:450W (Normal Mode), 340W (Eco. Mode), Standby <0.5W
	<b>Lamp Life and Type</b>	1,500/3,500 hours (Normal/Eco. Mode) 370W / 280W
	<b>Speakers</b>	3W x 2 (Stereo)
	<b>Noise Level</b>	42dB/37dB (Normal/Eco. Mode)
	<b>Standard Accessories</b>	VGA Cable, User Manual (CD), Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Spare Lamp P/N (5811118452-SVV (Non-Tilt Lamp), 5811118482-SVV (Tilt Lamp)), Remote Control P/N (5041825300)
	<b>Warranty</b>	Large Venue Warranty: 5 years projector / 1 year on lamp or 1000 hours whichever comes first
	<b>UPC Code</b>	814964 338815

## OPTIONAL LENSES

Lens Name	Standard Lens	Wide Fix	Long Zoom 1	Long Zoom 2	Short Throw
<b>Aspect Ratio</b>	16:10	16:10	16:10	16:10	16:10
<b>Throw Ratio</b>	1.54 - 1.93:1	0.78:1	1.93 - 2.89:1	3.0-5.0:1	1.1-1.3:1
<b>Projection Distance</b>	1.5m-7m	0.5m-3m	2m-20m	3m-20m	1m-9m
<b>Image Size</b>	30-300	25-200	30-500	35-400	30-300
<b>Zoom</b>	-	-	-	-	-
<b>F Number</b>	-	-	2.5 - 3.1	-	2.05 - 2.27
<b>Focal Length</b>	-	-	28.5 - 42.75 mm	44.5 - 74.19 mm	16.64 - 19.54 mm
<b>Part Number</b>	5811116223-SU (LNS-5SZ1)	5811120818-SVV (VL904G/LNS-5FX2)	5811116224-SU (LNS-5LZ1)	5811120055-SVV (LNS-5LZ2)	5811120054-SVV (LNS-5STZ)